



EU Declaration of Conformity



Name of the Manufacturer	Shenzhen Qianyan Technology LTD
Address of the Manufacturer	No. 3301,Block C,Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street
Name of the Product	Govee Table Lamp 2
Trade Mark	Govee
Model	H6022

We Shenzhen Qianyan Technology LTD declare under our sole responsibility that the above referenced product is in conformity with the applicable requirements of the following directives:

Low Voltage Directive: 2014/35/EU

Radio Equipment Directive: 2014/53/EU

RoHS Directive:2011/65/EU

Ecodesign Directive 2009/125/EC

COMMISSION REGULATION (EU) 2019/2020

COMMISSION REGULATION (EU) 2021/341

COMMISSION DELEGATED REGULATION (EU) 2019/2015


COMMISSION DELEGATED REGULATION (EU) 2021/340

Conformity with these directives has been assessed for the product by demonstrating compliance to the following harmonized standards and/or regulations:

Standards	
Safety	EN IEC 62368-1:2020+A11:2020 EN IEC 60598-1: 2021+A11:2022 EN 60598-2-4:2018 EN IEC 62031:2020+A11:2021 EN 62493: 2015
EMC	EN IEC 62311: 2020
Health	ETSI EN 301 489-1 V2.2.3 (2019-11) ETSI EN 301 489-17 V3.2.4(2020-09) EN IEC 55015: 2019+A11:2020 EN IEC 61000-3-2: 2019+A1: 2021 EN 61000-3-3:2013+A2:2021 EN 61547:2009
Radio	ETSI EN 300 328 V2.2.2 (2019-07)
RoHS	IEC 62321-3-1:2013, IEC 62321-5:2013, IEC 62321-4:2013+AMD1:2017,IEC 62321-7-1:2015, IEC 62321-7-2:2017, IEC 62321-6:2015, IEC 62321-8:2017
	EN 61000-3-2: 2014, EN 60081:1998+A11:2018

ErP	EN 13032-1:2004+A1:2012, EN 13032-4:2015+A1:2019 EN 62722-1:2016, EN 62722-2-1:2016
-----	--

Signed for and on behalf of: Shenzhen Qianyan Technology LTD.

Title:	Certification Manager	Function:	Certification
Name:	Panxiaopeng	Signature:	
City:	Shenzhen	Date:	2024-09-06

Exemptions for Energy Efficiency

A colour-tuneable light sources that can be set to at least the colours listed in this point and which have for each of these colours, measured at the dominant wavelength, excitation purity of

Colour	Wavelength	Excitation Purity
Blue	440nm-490nm	90%
Green	520nm-570nm	65%
Red	610nm-670nm	95%

and are intended for use in applications requiring high-quality coloured light;